

Product Specification

10Gbps 40KM SFP+ Transceiver

CLSFP1510GER

V20160818

Product Features

- Up to 10Gbps data links
- 40km with 9/125μm SMF
- 1550nm EML laser
- Duplex LC Connector
- Hot-pluggable SFP+ footprint
- Single 3.3V power supply
- Operating temperature: 0°C to 70°C
- RoHS
- Digital Diagnostic Monitor(DDM)
- Power Consumption < 1.2W



Applications

√ 10GBase-ER/EW 10GEthernet

1. Absolute Maximum Ratings

Parameter	Symbol	Min.	Max.	Unit
Supply Voltage	Vcc	-0.5	4	V
Storage Temperature	Ts	-40	85	°C
Operating Case Temperature	Tc	0	70	°C

2. Recommended Operating Conditions

Parameter	Symbol	Min.	Typical	Max.	Unit
-----------	--------	------	---------	------	------

Operating Temperature	Case	Tc	0		70	°C
Power Supply Voltage		Vcc	3.15	3.3	3.45	V
Power Supply Current		Icc			450	mA
Data Rate				10		GBps
Max Link Length on 9/125µm SMF		Lmax			40	km

3. Optical Characteristics

Parameter	Symbol	Min.	Typical	Max.	Unit
Transmitter					
Centre Wavelength	λ_c	1510	1550	1570	nm
Spectral Width (-20dB)	σ			1	nm
Average Output Power	Pout	-2		5	dBm
Extinction Ratio	ER	8.2			dB
Average Launch Power of Off Transmitter	Poff			-30	dBm
Receiver					
Centre Wavelength	λ_c	1200	1550	1600	nm
Receiver Sensitivity	PIN			-16	dBm
Receiver Overload	Pmax	-1			dBm
LOS De-Assert	LOSD			-21	dBm
LOS Assert	LOSA	-23			dBm
LOS Hysteresis		0.5		4.5	dB

4. Electrical Characteristics

Parameter	Symbol	Min.	Typical	Max.	Unit
Transmitter					
Input Differential Impedance	Zin	90	100	110	Ω
Data Input Swing Differential	Vin	250		1200	mV
Tx-Dis Disable	Vd	2.0		Vcc	V
Tx-Dis Enable	Ven	0		0.8	V
Receiver					
Data Output Swing Differential	Vout	250		800	mV

Rx-Los Fault	Vlf	2.0		VcchOST	V
Rx-Los Normal	Vln	0		0+0.8	V
Output rise and fall time	Tr, Tf	30			ps

5. Pin Descriptions




Diagram of Host Board Connector Block Pin Numbers and Names

Pin	Symbol	Description	Ref.
1	VEET	Transmitter Ground (Common with Receiver Ground)	7.1
2	TFAULT	Transmitter Fault. Not supported.	
3	TDIS	Transmitter Disable. Laser output disabled on high or open.	7.2
4	MOD_DEF(2)	Module Definition 2. Data line for Serial ID.	7.3
5	MOD_DEF(1)	Module Definition 1. Clock line for Serial ID.	7.3
6	MOD_DEF(0)	Module Definition 0. Grounded within the module.	7.3
7	RS0	Rate Select0, optionally controls SFP+ module receiver. When high input signaling rate > 4.25 GBd and when low input signaling rate < 4.25 GBd	

8	LOS	Loss of Signal indication. Logic 0 indicates normal operation.	7.4
9	RS1	Rate Select1, optionally controls SFP+ module receiver. When high input signaling rate > 4.25 GBd and when low input signaling rate < 4.25 GBd	
10	VEER	Receiver Ground (Common with Transmitter Ground)	7.1
11	VEER	Receiver Ground (Common with Transmitter Ground)	7.1
12	RD-	Receiver Inverted DATA out. AC Coupled.	
13	RD+	Receiver Non-inverted DATA out. AC Coupled.	
14	VEER	Receiver Ground (Common with Transmitter Ground)	7.1
15	VCCR	Receiver Power Supply	
16	VCCT	Transmitter Power Supply	
17	VEET	Transmitter Ground (Common with Receiver Ground)	7.1
18	TD+	Transmitter Non-Inverted DATA in. AC Coupled.	
19	TD-	Transmitter Inverted DATA in. AC Coupled.	
20	VEET	Transmitter Ground (Common with Receiver Ground)	7.1

Notes:

- 5.1 Circuit ground is internally isolated from chassis ground.
- 5.2 Laser output disabled on TDIS > 2.0V or open, enabled on TDIS < 0.8V.
- 5.3 Should be pulled up with 4.7k - 10kohms on host board to a voltage between 2.0V and 3.6V. MOD_DEF(0) pulls line low to indicate module is plugged in.
- 5.4 LOS is open collector output. Should be pulled up with 4.7k - 10kohms on host board to a voltage between 2.0V and 3.6V. Logic 0 indicates normal operation; logic 1 indicates loss of signal.

6. EEPROM & DDM THRESHOLD

6.1 EEPROM

2 wire address 1010000X (A0h)


0~95	Serial ID Defined by SFP MSA (96 bytes)
96~127	Vendor Specific (32 bytes)
128~255	

Reserved (128 bytes)

6.1 DDM THRESHOLD

	Low Alarm	Low Warn	High Warn	High Alarm
Temperature	-6°C	0°C	70°C	75°C
Voltage	3V	3.1V	3.5V	3.6V
Tx Bias	15mA	20mA	90mA	100mA
Tx Power	-8.5dBm	-4.5dBm	4dBm	6.5dBm
Rx Power	-20dBm	-15.5dBm	-1dBm	1.5dBm

7. Mechanical Specifications



8. LABEL

C-LIGHT offers label OEM design and print.
 Label barcode supports code128 and 2D barcode
 SIZE: 26mm*10.5mm

C-LIGHT



Ordering Information

Part No.	Data Rate	DDM	Wave	Fiber Type	Dist.	Temp.	Optical Interface
CLSFP1510GER	10Gbps	yes	1550nm	SMF	40km	0~70°C	LC

VERSION UPDATE:

VERSION NO.	DATE	UPDATED INFORMATION
V20160818	20160818	<ol style="list-style-type: none">EEPROM& DDM Threshold updated"LABEL" addedOrdering information updatedProduct picture updated

NOTICE:

C-LIGHT reserves the right to make changes to this product in this specification without notice, in order to improve product performance.

CONTACT:

Shenzhen C-Light network communication co., Ltd

4F East, Building 1, Shunheda Factory Plant, Liuxiandong industrial park,
Xili, Nanshan Dist, Shenzhen PR. China

Tel: 86-755-2778-9180 **Fax:** 86-755-2778-9174

E-mail: sales@c-light.com <http://www.c-light.com>