

100G QSFP28 ER4 40KM Transceiver CL100GQSFPER4

Product Features:

- Compliant with QSFP28 Standard: SFF-8661 Rev 2.5, SFF-8636 Rev 2.10a
- High speed I/O electrical interface (CAUI-4) compliant with IEEE 802.3bm-2015
- Compliant with 100GBASE-ER4 Lite standard
- Single 3.3V Supply Voltage
- Maximum power consumption 5.5 W at 70°C Case Operating Temperature
- LAN WDM EML laser and APD Receiver
- Universal QSFP28 MSA package with duplex LC connector
- Two Wire Serial Interface with Digital Diagnostic Monitoring
- Complies with EU Directive 2011/65/EU (RoHS compliant)
- Class 1 Laser



Functional Characteristics (Optical)

The following tables list the performance specifications for the various functional blocks of the integrated optical transceiver module.

Table 1 – Transmitter Optical Specifications

Parameter	Symbol	Min.	Typical	Max.	Unit	Notes
Wavelength L0	λ_{C0}	1294.53	1295.56	1296.59	nm	
Wavelength L1	λ_{C1}	1299.02	1300.05	1301.09	nm	
Wavelength L2	λ_{C2}	1303.54	1304.58	1305.63	nm	
Wavelength L3	λ_{C3}	1308.09	1309.14	1310.19	nm	
Side-mode suppression ratio	SMSR	30			dB	
Total Average Optical Launch Power	POUT	-	-	12	dBm	
Average Launch Power Tx_Off (Each Lane)	POUT_OFF	-	-	-30	dBm	
Average Optical Launch Power (Each Lane)	POUTL	-2	-	5	dBm	
Extinction Ratio	ER	8	-	-	dB	
Optical Modulation Amplitude (Each Lane)	OMA	0.1	-	4.5	dBm	
Transmitter and Dispersion Penalty (Each Lane)	TDP	-	-	2.5	dB	
Difference in launch power between any two lanes (Average and OMA)	DT_OMA	-	-	3.6	dB	
Optical Return Loss Tolerance	ORLT	-	-	20	dB	
RIN20OMA	RIN	-	-	-130	dB/Hz	



Transmitter Reflectance	TR	-	-	-26	dB	
Transmitter Eye Mask Definition	-	{0.25, 0.4, 0.45, 0.25, 0.28, 0.4}				

Table 2 – Receiver Optical Specifications

Parameter	Symbol	Min.	Typical	Max.	Unit	Notes
Wavelength L0	λ_{C0}	1294.53	1295.56	1296.59	nm	
Wavelength L1	λ_{C1}	1299.02	1300.05	1301.09	nm	
Wavelength L2	λ_{C2}	1303.54	1304.58	1305.63	nm	
Wavelength L3	λ_{C3}	1308.09	1309.14	1310.19	nm	
Receiver Sensitivity (OMA) per Lane				-21.4	dBm	Note 1
Stressed Receiver Sensitivity in OMA (Each Lane)	-	-	-	-18	dBm	Note 1
Stressed Receiver Sensitivity Test Conditions:						
Stressed Eye J2 Jitter (Each Lane)	-	-	0.3	-	UI	
Stressed Eye J9 Jitter (Each Lane)	-	-	0.47	-	UI	
Vertical Eye Closure Penalty	-	-	3.5	-	dB	
Damage Threshold for Receiver	Pin, damage	-4	-	-	dBm	
Average Receive Power (Each Lane)	-	-20.9	-	-4.5	dBm	
Receive Power in OMA (Each Lane), Overload	OMA	-	-	-4.5	dBm	
Receiver Reflectance	RXR	-	-	-26	dB	

Note 1: Measured with conformance test signal at TP3 for the BER = 1x10⁻¹²

Ordering Information

Table 3 - Ordering Information

Part No.	Application	Data Rate	Laser Source	Fiber Type
CL100GQSFPER4	100GBASE-ER4	100Gb Ethernet	EML	Single Mode Fiber

CONTACT:

Email: sales@c-light.com <https://www.c-light.com>