

10G 10KM SFP+ Transceiver CLSFP1310GLR

Product Features

- Up to 10Gbps data links
- 10km with 9/125μm SMF
- 1310nm DFB laser
- Duplex LC Connector
- Hot-pluggable SFP+ footprint
- Single 3.3V power supply
- Operating temperature: 0°C to 70°C
- RoHS
- Digital Diagnostic Monitor compatible
- Power Consumption < 0.8W



Functional Characteristics (Optical)

The following tables list the performance specifications for the various functional blocks of the integrated optical transceiver module.

Table 1 – Transmitter Optical Specifications

Parameter	Symbol	Min.	Typical	Max.	Unit
Centre Wavelength	λ_c	1260	1310	1360	nm
Spectral Width (-20dB)	σ			1	nm
Average Output Power	P _{out}	-5		0	dBm
Extinction Ratio	ER	3.5			dB
Average Launch Power of Off Transmitter	P _{off}			-30	dBm

Note 1: Average launch power, each lane (min) is informative and not the principal indicator of signal strength

Note 2: Transmitter reflectance is defined looking into the transmitt

Table 2 – Receiver Optical Specifications

Parameter	Symbol	Min.	Typical	Max.	Unit
Centre Wavelength	λ_c	1200	1310	1600	nm
Receiver Sensitivity	PIN			-14	dBm
Receiver Overload	P _{max}	0.5			dBm
LOS De-Assert	LOSD			-19	dBm
LOS Assert	LOSA	-24			dBm
LOS Hysteresis		0.5		4.5	dB

Note 1: Measured with conformance test signal at TP3 for the BER= 6.4x10⁻⁵.

Ordering Information



Table 3 - Ordering Information

Part No.	Data Rate	DDM	Wave	Fiber Type	Dist.	Temp.	Optical Interface
CLSFP1310GLR	10Gbps	yes	1310nm	SMF	10km	0~70℃	LC

CONTACT:

Email: sales@c-light.com <https://www.c-light.com>