

100Gbps QSFP28 ER4 60km Transceiver FEC FREE Version

CL100GQSFP28ER4-60

Product Features:

- Compliant with QSFP28 Standard:
- SFF-8661 Rev 2.5, SFF-8636 Rev 2.10a
- High speed I/O electrical interface (CAUI-4) compliant with IEEE 802.3bm-2015
- 100GBASE-ER4 103.125G 60km point-to-point Ethernet links
- Up to 60km SMF without FEC
- Single 3.3V Supply Voltage
- LAN WDM EML cooled laser and SOA+PIN cooled Receiver
- Universal QSFP28 MSA package with duplex LC connector
- Two Wire Serial Interface with Digital Diagnostic Monitoring
- Complies with EU Directive 2011/65/EU (RoHS compliant)
- LPMODE, ModPrsL, ModSelL and ResetL are supported
- Telecom networking
- Class 1 Laser

Functional Characteristics (Optical)

The following tables list the performance specifications for the various functional blocks of the integrated optical transceiver module.

Table 1 – Transmitter Optical Specifications

Parameter	Symbol	Min.	Typical	Max.	Unit	Notes
Wavelength L0	λ_{C0}	1294.53	1295.56	1296.59	nm	
Wavelength L1	λ_{C1}	1299.02	1300.05	1301.09	nm	
Wavelength L2	λ_{C2}	1303.54	1304.58	1305.63	nm	
Wavelength L3	λ_{C3}	1308.09	1309.14	1310.19	nm	
Side-mode suppression ratio	SMSR	30			dB	
Total Average Optical Launch Power	POUT	-	-	12.5	dBm	
Average Launch Power Tx_Off (Each Lane)	POUT_OFF	-	-	-30	dBm	
Average Optical Launch Power (Each Lane)	POUTL	0	-	5	dBm	
Extinction Ratio	ER	8	-	-	dB	
Spectral Width	$\Delta\lambda$	-	-	1	nm	
Optical Modulation Amplitude(Each Lane)	OMA	0	-	6.5	dBm	
Launch Power in OMA minus TDP (Each Lane)	OMA-TDP	0	-	-	dBm	
Difference in launch power between any two lanes(OMA)	DT_OMA	-	-	2.5	dB	
Optical Return Loss Tolerance	ORLT	-	-	20	dB	



RIN20OMA	RIN	-	-	-130	dB/H z	
Transmitter Reflectance	TR	-	-	-12	dB	
Transmitter Eye Mask Definition	-	IEEE 802.3bs-2010 {0.25, 0.4, 0.45, 0.25, 0.28, 0.4}				

Table 2 – Receiver Optical Specifications

Parameter	Symbol	Min.	Typical	Max.	Unit	Notes
Wavelength L0	λ_{C0}	1294.53	1295.56	1296.59	nm	
Wavelength L1	λ_{C1}	1299.02	1300.05	1301.09	nm	
Wavelength L2	λ_{C2}	1303.54	1304.58	1305.63	nm	
Wavelength L3	λ_{C3}	1308.09	1309.14	1310.19	nm	
Receiver Sensitivity (OMA) per Lane @5E-5				-27	dBm	
60km SMF Receiver Sensitivity in OMA Per Lane @1E-12	-	-	-	-20	dBm	
Saturation Power, each lane	SP	-4.5			dBm	
Damage Threshold for Receiver	Pin, damage	0	-	-	dBm	
Average Receive Power (Each Lane)	-	-32	-	-4.5	dBm	
Receive Power in OMA (Each Lane), Overload	OMA	-	-	-4.5	dBm	
LOS Assert	LOSA	-40	-	-	dBm	
LOS De-assert	LOSD	-	-	-30	dBm	
LOS hysteresis	LOSH	0.5	-	-	dB	

Ordering Information

Table 3 - Ordering Information

Part No.	Data Rate	DDM	Wave	Fiber Type	Dist.	Temp.	Optical Interface
CL100GQSFP SER4-60	100Gbps	yes	1310nm	SMF	60km Without FEC	0~70°C	LC

CONTACT:

Email: sales@c-light.com <https://www.c-light.com>