1Gbps~10Gbps 1310nm MMF 300m SFP+
CLSFP1310GLRM

Product Features:

- 1Gbps~10Gbps data links
- Reach 300m on OM3 MMF
- 1310nm laser
- Duplex LC Connector
- Hot-pluggable SFP+ footprint
- Single 3. 3V power supply
- Operating temperature: 0°C to 70°C
- RoHS
- Digital Diagnostic Monitor compatible
- Power Consumption < 0.8W

Functional Characteristics (Optical)

The following tables list the performance specifications for the various functional blocks of the integrated optical transceiver module.

Table 1 – Transmitter Optical Specifications

Parameter	Symbol	Min.	Typical	Max.	Unit
Centre Wavelength	λc	1260	1310	1360	nm
Spectral Width (-20dB)	σ			1	nm
Average Output Power	Pout	-7		0	dBm
Extinction Ratio	ER	3.5			dB
Average Launch Power of Off Transmitter	Poff			-30	dBm

Table 2 – Receiver Optical Specifications

Parameter	Symbol	Min.	Typical	Max.	Unit
Centre Wavelength	λc	1200	1310	1600	nm
Receiver Sensitivity	PIN			-11	dBm
Receiver Overload	Pmax	0.5			dBm
LOS De-Assert	LOSD			-20	dBm
LOS Assert	LOSA	-23			dBm
LOS Hysteresis		0.5		4.5	dB

Ordering Information

Table 3 - Ordering Information

Part No.	Data Rate	DDM	Wave	Fiber Type	Dist.	Temp.	Optical Interface
CLSFP1310GLRM	10Gbps	yes	1310nm	MMF	300m	-40~85℃	LC

CONTACT:

Email: sales@c-light.com https://www.c-light.com