10Gbps 80KM SFP+ Transceiver

CLSFP1510GZR-S

Product Features:

- Up to 10Gbps data links
- 80km with 9/125μm SMF
- 1550nm EML laser
- APD receiver
- Duplex LC Connector
- Hot-pluggable SFP+ footprint
- Single 3. 3V power supply
- Operating temperature: -40℃ to 100℃
- RoHS
- Digital Diagnostic Monitor(DDM)
- Power Consumption < 1.5W

Functional Characteristics (Optical)

The following tables list the performance specifications for the various functional blocks of the integrated optical transceiver module.

Table 1 – Transmitter Optical Specifications

Parameter	Symbol	Min.	Typical	Max.	Unit
Centre Wavelength	λc	1530	1550	1570	pm
Spectral Width (-20dB)	σ			1	nm
Average Output Power	Pout	0		5	dBm
Extinction Ratio	ER	8.2			dB
Average Launch Power of Off Transmitter	Poff			-30	dBm

Table 2 – Receiver Optical Specifications

Parameter	Symbol	Min.	Typical	Max.	Unit
Centre Wavelength	λc	1200	1550	1600	nm
Receiver Sensitivity	PIN			-25	dBm
Receiver Overload	Pmax	-7			dBm
LOS De-Assert	LOSD			-35	dBm
LOS Assert	LOSA	-37			dBm
LOS Hysteresis		0.5		4.5	dB

Ordering Information

Table 3 - Ordering Information

Part No.	Data Rate	DDM	Wave	Fiber Type	Dist.	Temp.	Optical Interface
CLSFP1510GZR-S	10Gbps	yes	1550nm	SMF	80km	-40~100℃	LC

CONTACT:

Email: sales@c-light.com https://www.c-light.com