

10Gbps 1550nm 40KM XFP Transceiver CLXFP1510GER

Product Features:

- 9.95Gbps to 11.1Gbps data links
- 40km with 9/125μm SMF
- 1550nm EML laser
- Duplex LC Connector
- Hot-pluggable XFP footprint
- Single 3.3V power supply
- Operating temperature: 0°C to 70°C
- RoHS
- Digital Diagnostic Monitor (DDM)
- Power Consumption < 1.5W

Functional Characteristics (Optical)

The following tables list the performance specifications for the various functional blocks of the integrated optical transceiver module.

Table 1 – Transmitter Optical Specifications

Parameter	Symbol	Min.	Typical	Max.	Unit
Centre Wavelength	λ_c	1530	1550	1560	nm
Spectral Width (-20dB)	σ			1	nm
Average Output Power	P _{out}	-1		5	dBm
Extinction Ratio	ER	8			dB
Average Launch Power of Off Transmitter	P _{off}			-30	dBm

Table 2 – Receiver Optical Specifications

Parameter	Symbol	Min.	Typical	Max.	Unit
Centre Wavelength	λ_c	1270		1600	nm
Receiver Sensitivity	PIN			-18	dBm
Receiver Overload	P _{max}	1			dBm
LOS De-Assert	LOSD			-22	dBm
LOS Assert	LOSA	-30			dBm
LOS Hysteresis		0.5			dB



Ordering Information

Table 3 - Ordering Information

Part No.	Data Rate	DDM	Wave	Fiber Type	Dist.	Temp.	Optical Interface
CLXFP1510GER	9.95Gbps ~11.1Gbps	yes	1550nm	SMF	40km	0~70°C	LC

CONTACT:

Email: sales@c-light.com <https://www.c-light.com>