

OTU4/ 25GBE/ 32G FC 1310nm 60km SFP Transceiver CLSFP32GMR60

Product Features:

- 28.05Gbps/27.95Gbps/25.78Gbps data rate with dual CDR mode
- 14.025Gbps/8.5Gbps with CDR bypass mode
- Hot-pluggable SFP28 footprint
- Built-in digital diagnostic functions
- 1310nm DFB laser transmitter + APD receiver
- Duplex LC connector
- RoHS compliant
- Up to 60km on 9/125μm SMF
- Single 3.3V power supply
- Operating temperature range: 0°C to 70°C
- Compliant with SFF-8402/8432/8472

Functional Characteristics (Optical)

The following tables list the performance specifications for the various functional blocks of the integrated optical transceiver module.

Table 1 – Transmitter Optical Specifications

Parameter	Symbol	Min	Typ	Max	Unit	Ref.
Average Output Power	POUT	+5		+8	dBm	1, 2
Optical Wavelength	Wave		1310		nm	
Spectral Width (-20dB)	σ			1	nm	
Side Mode Suppression Ratio	SMSR	30			dB	
Optical Modulation Amplitude	OMA	+3		+8	dBm	
Transmitter Dispersion Penalty @ 8.5 Gb/s 14.025Gb/s 25Gb/s 28.05Gb/s	TDP			3.0 3.5 2.5 2.5	dB	
Extinction Ratio	ER	4			dB	
Relative Intensity Noise	RIN			-130	dB/Hz	

Table 2 – Receiver Optical Specifications

Parameter	Symbol	Min	Typ	Max	Unit	Ref.
Unstressed Receiver OMA Sensitivity 8.5 Gb/s 14.025Gb/s 25Gb/s 28.05Gb/s	RxSENS			-16.5 -16.5 -16.0 -15.5	dBm	3
Receiver Optical Modulation Amplitude	RxMAX			2	dBm	4
Stress Receiver Sensitivity				-9.5	dBm	



Optical Return Loss 8.5Gb/s & 14.025Gb/s 25Gb/s 28.05Gb/s		12 26			dB	
LOS De-Assert	LOSD			-17	dBm	
LOS Assert	LOSA	-30			dBm	
LOS Hysteresis		0.5			dB	
Link Parameters						
Channel IL		5		13.2	dB	
Allocation of Penalties				2.7	dB	
Total Power Budget (Maximum TDP)				15.9	dB	



Ordering Information

Table 3 - Ordering Information

Part No.	Application	Data Rate	Laser	Fiber Type
CLSFP32GMR60	OTU4; FC 8/16/32G; 25GBase 60km	28.05Gbps Max	1310nm	Single Mode Fiber

CONTACT:

Email: sales@c-light.com <https://www.c-light.com>